



Swivels


Swivels—Not for Lifting




Galvanized Forged Steel Eye and Eye



Eye and Fork with Cotter Pin



Eye and Fork with Screw Pin



Fork and Fork

Use on rope and chain to relieve stress caused by twisting and knotting in pulling applications. Ideal for connecting two different ropes or chains. Work load limits are based on use in a straight line and should not be used at an angle. Swivels are not designed for spinning or rotating while under load. Not for lifting.

Eye and Eye— Extra-large eye opening for oversized chain and rope.

Eye and Fork— Use where frequent attachment and detachment is required. *Galvanized swivels* have a cotter pin; *stainless steel swivels* have a screw-pin clevis.

Fork and Fork— Perfect for connecting combinations of chain and fittings. Screw pin allows quick and easy attachment without tools.

Eye and Eye

Dia.	(A)	(B)	(C)	(D)	(E)	Work Load Limit, lbs.	Each
Galvanized Forged Steel							
1/4"	3 3/8"	3/4"	3/4"	1 1/16"	3/4"	850	3552T14 \$13.50
5/16"	4 1/8"	3/4"	1"	1 1/4"	1"	1,250	3552T15 14.62
3/8"	5"	1"	1 1/4"	1 1/2"	1 1/4"	2,250	3552T16 17.43
1/2"	6 3/4"	1 1/4"	1 1/2"	1 15/16"	1 1/2"	3,600	3552T17 21.54
5/8"	8"	1 5/8"	1 3/4"	2 3/8"	1 3/4"	5,200	3552T18 34.37
3/4"	8 3/4"	1 3/4"	2"	2 1/2"	2"	7,200	3552T19 43.59
7/8"	10 3/8"	2 1/8"	2 1/4"	3 1/16"	2 1/4"	10,000	3552T21 79.14
1"	11 3/4"	2 1/4"	2 1/2"	3 1/2"	2 1/2"	12,500	3552T22 91.98
1 1/4"	13 15/16"	3 1/4"	3 1/8"	3 7/8"	3 1/8"	18,000	3552T24 167.00
Cast Type 316 Stainless Steel							
3/16"	2 5/16"	1/2"	1/2"	1/2"	1/2"	297	3714T91 6.57
1/4"	2 9/16"	5/8"	5/8"	5/8"	5/8"	396	3714T92 6.88
5/16"	3 1/2"	13/16"	3/4"	13/16"	3/4"	673	3714T93 8.73
3/8"	3 15/16"	1 1/8"	15/16"	1 1/8"	15/16"	1,192	3714T94 12.27
1/2"	5 7/8"	1 5/16"	1 3/8"	1 5/16"	1 3/8"	2,871	3714T95 22.00
5/8"	7 1/4"	1 3/4"	1 1/2"	1 3/4"	1 1/2"	4,950	3714T96 40.74

Eye and Fork with Cotter Pin— Galvanized Forged Steel

Dia.	(A)	(B)	(C)	(D)	(E)	(F)	Work Load Limit, lbs.	Each
1/4"	3 5/32"	3/4"	3/4"	3/4"	1/2"	1/4"	850	3553T14 \$16.24
5/16"	3 3/4"	3/4"	1"	13/16"	1/2"	5/16"	1,250	3553T15 19.23
3/8"	4 5/8"	1"	1 1/4"	1 1/16"	11/16"	3/8"	2,250	3553T16 19.96
1/2"	6 1/8"	1 1/4"	1 1/2"	1 3/8"	3/4"	1/2"	3,600	3553T17 28.11
5/8"	7 3/8"	1 5/8"	1 3/4"	1 1/2"	15/16"	5/8"	5,200	3553T18 44.57
3/4"	8"	1 3/4"	2"	1 3/4"	1 1/8"	3/4"	7,200	3553T19 57.06
7/8"	9 3/8"	2 1/8"	2 1/4"	2 1/16"	1 3/16"	7/8"	10,000	3553T21 95.18
1"	11 7/16"	2 1/4"	2 1/2"	2 7/16"	1 3/4"	1 1/8"	12,500	3553T22 120.81
1 1/4"	12"	3 1/4"	3 1/8"	2 13/16"	2 1/16"	1 3/8"	18,000	3553T24 237.48

Eye and Fork with Screw Pin— Cast Type 316 Stainless Steel

Dia.	(A)	(B)	(C)	(D)	(E)	(F)	Work Load Limit, lbs.	Each
1/4"	2 5/8"	5/8"	9/16"	7/16"	1/2"	7/32"	770	30365T31 \$7.58
5/16"	3 5/8"	27/32"	5/8"	5/8"	5/8"	5/16"	1,430	30365T32 9.97
3/8"	4 13/32"	1 1/4"	15/16"	13/16"	3/4"	3/8"	2,200	30365T33 14.74
1/2"	5 3/4"	1 9/32"	1 5/16"	1"	1"	17/32"	3,080	30365T34 32.29
5/8"	7"	1 11/16"	1 1/2"	1 13/32"	1 7/32"	5/8"	5,500	30365T35 52.79
3/4"	8 1/4"	2"	1 19/32"	1 19/32"	1 3/8"	3/4"	8,800	30365T36 98.34